



## BM2012-A

### KEY FEATURES

- CE Cat II, EN388:2016+A1:2018, EN ISO 21420:2020
- ANSI/ISEA (A3) CUT
- High Cut Resistance (Cut Level C)
- Finger Dexterity Test (5)
- Nitrile Sandy for Excellent Grip
- Superior Flexibility and Comfort
- Optimum Mechanical Performance
- Washable and Breathable
- **TEAR RESISTANCE OVER 75N**
- **PUNCTURE RESISTANCE OVER 126N**
- **MAXIMUM ABRASION RESISTANCE (8000 CYCLES)**

### SPECIFICATION

- 13 Guage seamless HPPE liner
- Nitrile coated palm & finger tips
- Sandy palm and fingers giving great grip on dry, wet or oily surface applications
- Reinforced thumb crotch
- Elastic cuffs gives snug fit
- Very comfortable and flexible gloves
- Extremely durable

### SIZES

7/S | 8/M | 9/L | 10/XL

### PACKING

12 Prs / Pack - 120 Prs / Carton

### APPLICATIONS

- Oil & Gas
- General Maintenance
- Construction
- Light Assembly
- Small Parts Handling
- Automotive
- Logistics
- Food Industries



CUT PROTECTION



ELASTIC



ABRASION RESISTANT



LIGHT WEIGHT

EN 388:2016

+A1:2018

ANSI/ISEA




CAT II



4X43C



CUT



Coated finger tips




Seamless HPPE knit liner



Elastic cuffs



Full Nitrile coated palm



Reinforced thumb crotch